## AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 🔺 CH-1844 Villeneuve 🔺 +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



## Flight test report: EN 926-2:2013+A1:2021\* & NfL 2-565-20

				-								
Manufacturer BGD Gmb	н	Certification number	F	PG_1950.2022								
Address Am Gewer 9413 St-G		Flight test	1	11.03.2022								
Glider model Austria		Classification	Е	3								
•	24		-	-								
<b>-</b> ·		Representative		Tom								
Trimmer no		Place of test	<u>ر</u>	/illeneuve								
Folding lines used no												
Test pilot		Philippe Dupont	C	Claude Thurnheer								
Harness Harness to risers distance (cm) Distance between risers (cm)		Supair - Altiplume S 44 40		Advance - Success 4 M 44 44 85								
							Total weight in flight (kg)		65	d	C	
							1. Inflation/Take-off		Α			
							Rising behaviour		Smooth, easy and constant rising	А	Smooth, easy and constant rising	A
Special take off technique required		No	А	No	A							
2. Landing		Α										
Special landing technique required		No	А	No	A							
3. Speed in straight flight		Α										
Trim speed more than 30 km/h		Yes	A	Yes	A							
Speed range using the controls larger tha	n 10 km/h	Yes	A	Yes	A							
Minimum speed		Less than 25 km/h	A	Less than 25 km/h	A							
4. Control movement		Α										
Max. weight in flight up to 80 kg		Increasing / greater than EE am	^	not available	0							
Symmetric control pressure / travel Max. weight in flight 80 kg to 100 kg		Increasing / greater than 55 cm	A	not available	0							
Symmetric control pressure / travel		not available	0	Increasing / greater than 60 cm	А							
Max. weight in flight greater than 100 k	a	not available	U	increasing / greater than oo em	Λ							
Symmetric control pressure / travel	9	not available	0	not available	0							
5. Pitch stability exiting accelerated flig	ıht	A	Ű		Ũ							
Dive forward angle on exit		Dive forward less than 30°	А	Dive forward less than 30°	А							
Collapse occurs		No	А	No	А							
6. Pitch stability operating controls du flight	ing accelerated	Α										
Collapse occurs		No	А	No	A							
7. Roll stability and damping		Α										
Oscillations		Reducing	А	Reducing	А							
8. Stability in gentle spirals		Α										
Tendency to return to straight flight		Spontaneous exit	А	Spontaneous exit	A							
9. Behaviour exiting a fully developed	spiral dive	A										
Initial response of glider (first 180°)		Immediate reduction of rate of turn	А	Immediate reduction of rate of turn	A							
Tendency to return to straight flight		Spontaneous exit (g force decreasing, rate of turn decreasing)	A	Spontaneous exit (g force decreasing, rate of turn decreasing)	A							
Turn angle to recover normal flight		Less than 720°, spontaneous recovery	A	Less than 720°, spontaneous recovery	A							
10. Symmetric front collapse		В										
Approximately 30 % chord												
Entry		Rocking back less than $45^{\circ}$	А	Rocking back less than 45°	A							
Recovery		Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А							

\*This standard is NOT covered by accreditation D-IS-19457-01

Test Report generated automatically by AIR TURQUOISE SA, valid without signature Rev 07 | 04.03.2022 // ISO | 91.22 // Page 1 of 3

Dive forward angle on exit Change of course	Dive forward 0° to 30° Keeping course	A	Dive forward 0° to 30° Keeping course	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
At least 50% chord				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	А	Dive forward 0° to 30° / Keeping course	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
With accelerator				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in less than 3 s	A
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping	A	Dive forward 0° to 30° / Keeping	A
Dive forward angle of exit? Change of course	course	~	course	~
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
11. Exiting deep stall (parachutal stall)	A			
Deep stall achieved	Yes	А	Yes	А
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Change of course	Changing course less than 45°	A	Changing course less than 45°	A
Cascade occurs	No		No	A
12. High angle of attack recovery	A	~	NO	~
	A Spontaneous in less than 3 s	۸	Spontaneous in less than 3 s	^
Recovery Cascade occurs	No	A A	No	A
		A	NO	A
13. Recovery from a developed full stall				•
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Collapse	No collapse	A	No collapse	A
Cascade occurs (other than collapses)	No	A	No	A
Rocking back	Less than 45°	A	Less than 45°	A
Line tension	Most lines tight	A	Most lines tight	А
14. Asymmetric collapse	В			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	Less than 90° / Dive or roll angle 0° to 15°	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	A
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle $15^\circ$ to $45^\circ$	A	Less than 90° / Dive or roll angle $15^\circ$ to $45^\circ$	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle $15^{\circ}$ to $45^{\circ}$	A	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А

\*This standard is NOT covered by accreditation D-IS-19457-01 Test Report generated automatically by AIR TURQUOISE SA, valid without signature Rev 07 | 04.03.2022 // ISO | 91.22 // Page 2 of 3

Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
15. Directional control with a maintained asymmetric collapse	Α			
Able to keep course	Yes	А	Yes	А
$180^\circ$ turn away from the collapsed side possible in 10 s	Yes	А	Yes	А
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	More than 50 % of the symmetric control travel	A
16. Trim speed spin tendency	Α			
Spin occurs	No	А	No	А
17. Low speed spin tendency	А			
Spin occurs	No	А	No	А
18. Recovery from a developed spin	Α			
Spin rotation angle after release	Stops spinning in less than 90°	А	Stops spinning in less than 90°	А
Cascade occurs	No	А	No	А
19. B-line stall	А			
Change of course before release	Changing course less than 45°	А	Changing course less than 45°	А
Behaviour before release	Remains stable with straight span	А	Remains stable with straight span	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 0° to 30°	А
Cascade occurs	No	А	No	А
20. Big ears	В			
Entry procedure	Dedicated controls	А	Dedicated controls	А
Behaviour during big ears	Stable flight	А	Stable flight	А
Recovery	Recovery through pilot action in less than a further 3 s	В	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 0° to 30°	А
21. Big ears in accelerated flight	В			
Entry procedure	Dedicated controls	А	Dedicated controls	А
Behaviour during big ears	Stable flight	А	Stable flight	А
Recovery	Recovery through pilot action in	В	Spontaneous in less than 3 s	Α
	less than a further 3 s			
Dive forward angle on exit		А	Dive forward 0° to 30°	А
Dive forward angle on exit Behaviour immediately after releasing the accelerator while maintaining big ears	less than a further 3 s	A A	Dive forward 0° to 30° Stable flight	A A
Behaviour immediately after releasing the accelerator while	less than a further 3 s Dive forward 0° to 30°			
Behaviour immediately after releasing the accelerator while maintaining big ears	less than a further 3 s Dive forward 0° to 30° Stable flight			
Behaviour immediately after releasing the accelerator while maintaining big ears <b>22. Alternative means of directional control</b> 180° turn achievable in 20 s Stall or spin occurs	less than a further 3 s Dive forward 0° to 30° Stable flight A Yes No	A	Stable flight	A
Behaviour immediately after releasing the accelerator while maintaining big ears22. Alternative means of directional control180° turn achievable in 20 sStall or spin occurs23. Any other flight procedure and/or configuration described in the user's manual	less than a further 3 s Dive forward 0° to 30° Stable flight A Yes No 0	A A	Stable flight Yes No	A A
Behaviour immediately after releasing the accelerator while maintaining big ears22. Alternative means of directional control180° turn achievable in 20 sStall or spin occurs23. Any other flight procedure and/or configuration described in the user's manual Procedure works as described	less than a further 3 s Dive forward 0° to 30° Stable flight A Yes No 0 not available	A A A 0	Stable flight Yes No not available	A A
Behaviour immediately after releasing the accelerator while maintaining big ears22. Alternative means of directional control180° turn achievable in 20 sStall or spin occurs23. Any other flight procedure and/or configuration described in the user's manual	less than a further 3 s Dive forward 0° to 30° Stable flight A Yes No 0	A A A	Stable flight Yes No	A A A